



OVP功能可由INN Pin或OCP Pin去完成, 但不會有Shutdown功能, 當LED開路時, Output電壓會維持在所設計的OVP電壓點.

	R14	R13	D3	D4	V-OVP
No-OCP Function	NC	0Ω	20KΩ	NC	$(V_z + 0.5) \times (R3 + R4) / R4$
OCP + OVP Achieve OVP by INN pin	100K	ON	24V	ON	$(V_z + 0.5) \times (R3 + R4) / R4$
OCP + OVP Achieve OVP by OCP pin	100K	ON	NC	24V	$(V_z + 0.2) \times (R3 + R4) / R4$

$R = R7 // R8 // R9 // R10 // R11 // R12$
 $R = 0.2 / I-LED$

The circuit furnished in this document is the property of BITEK and SHOULD be treated as highly confidentiality; ANY UNAUTHORIZED DISCLOSURE, COPYING, DISTRIBUTION OR USE IS STRICTLY PROHIBITED. The receiver shall fully compensate BITEK without any reservation for any losses thereof due to its violation of BITEK's confidential request. Further, the receiver is deemed to agree on BITEK's confidential request therein otherwise the receiver shall return this document to BITEK immediately. BITEK is not responsible for any possibly infringement of intellectual property rights owned by any third party that may arise from the use of these circuits.

Beyond Innovation Technology Co., LTD.
 4F, No.16, Sec.4, Nanjing E. Road, Taipei, Taiwan, R.O.C.
 Tel : 886-2-2570-5818 Fax : 886-2-2570-8118

Title			
BIT3260+B0210D Demo board			
Size	Document Number	Task Code	Rev
Custom	INV-1123-100-242		1.1
Date:	Friday, February 24, 2012	Sheet 1 of 1	